



POWER INVERTER

RG-HK SERIES

Smart Control

- Three smart control mode,auto switch for different demand

Stable & Durable

- Inbuilt toroidal transformer,triple surge power, stable and durable

Battery Type

- Support SLA/GEL/AGM battery



MODEL	RG-HK600W	RG-HK700W	RG-HK1000W	RG-HK1200W
Rated power	600W	700W	1000W	1000W
Surge power	1800W	2100W	3000W	3600W
AC Input & Output				
Voltage	220VAC			
Selectable Voltage Range	145-275VAC(220VAC)			
Frequency Range	50Hz/60Hz automatic recognition			
AC Voltage Regulation (BATT.Mode)	(DC Batt.mode) 220vac±3%			
Transfer Time	≤8ms			
Wave Form	Pure Sine Wave			
Transformer type	Toroidal			
Transfer efficiency	≥85%			
Battery				
Battery Voltage	12V./24V			
Type	GEL/SLA/AGM/Water battery			
DC Charge Voltage	13.8VDC(12V)/27.6VDC(24V)			
Overcharge Protection	Battery voltage≥16VDC(12V)≥32VDC(24V),stop charging after 60s alarm			
AC Charger				
Maximum Ac Charge Current	15A			
Working mode				
01 mode	AC priority mode			
02 mode	ECO mode			
03 mode	Battery priority mode			
04 mode	Unattended mode			
Physical				
Dimension, D*W*H(MM)	290x258x125			
N.W.(KGS)	6.7	7.2	7.6	8.2
Environment				
Humidity	0~95%(NO condensation)			
Operating Temperature	0~60℃			
Storage Temperature	0~60℃			

***Product Specifications Are Subject To Change Without Further Notice**